

Docket No. AUS9-2000-0546-US1

CLAIMS:

What is claimed is:

- 5 1. A method for processing foreign protocol requests across a system area network, the method comprising:
receiving a request from a device utilizing a protocol which is foreign to a protocol utilized by the system area network;
10 encapsulating the request in a data packet; and
sending the data packet to a requested node via the system area network fabric.
- 15 2. The method as recited in claim 1, wherein the request is a first request, the data packet is a first data packet, and the sending the data packet comprises sending the data packet on a first virtual lane, and further comprising:
receiving a second request from a device utilizing a
20 protocol which is foreign to the protocol utilized by the system area network;
encapsulating the second request in a second data packet; and
responsive to a determination that the first and
25 second requests are to be kept in order, sending the second data packet to a requested node via the first virtual lane on the system area network fabric.
- 30 3. The method as recited in claim 1, wherein the request is a first request, the data packet is a first data packet, and the sending the data packet comprises

007349913000
0020218662200

Docket No. AUS9-2000-0546-US1

sending the data packet on a first virtual lane, and further comprising:

receiving a second request from a device utilizing a protocol which is foreign to the protocol utilized by the
5 system area network;

encapsulating the second request in a second data packet; and

responsive to a determination that the first and second requests should be able to bypass the other,
10 sending the second data packet to a requested node via a second virtual lane on the system area network fabric.

4. The method as recited in claim 1, wherein the request is an interrupt received by a target channel
15 adapter and further comprising:

receiving the data packet, at a host channel adapter, and decoding the data packet to retrieve the interrupt; and

interrupting the processor.
20

5. The method as recited in claim 4, wherein the data packet is a first data packet and further comprising:

receiving, at the host channel adapter, an end of interrupt instruction;
25 encapsulating the end of interrupt instruction into a second data packet; and

transmitting the second data packet to the target channel adapter via the system area network fabric.

6. The method as recited in claim 5, further comprising:
30

00734989-130700

[illegible]

k

5

10

Р

15

20

r

25

12. The method as recited in claim 8, wherein the steps

12. The method as recited in claim 8, wherein the steps

across a system area network, the method comprising:

- receiving a data packet from a system area network fabric;
- determining that the data packet contains an encapsulated foreign protocol transmission;
- decoding the data packet to obtain the foreign protocol transmission; and
- sending the foreign protocol transmission to a requested device.

19. The method as recited in claim 18, wherein the foreign protocol is a peripheral component interconnect bus protocol.

20. The method as recited in claim 18, wherein the requested device is an input/output adapter.

21. The method as recited in claim 18, wherein the steps of receiving, determining, decoding, and sending are performed by a target channel adapter.

22. The method as recited in claim 18, wherein the steps of receiving, determining, decoding, and sending are performed by a host channel adapter.

23. The method as recited in claim 22, wherein the step of sending comprises converting the foreign protocol request to an appropriate host transaction.

24. A computer program product in a computer readable media for use in a networked data processing system for

processing foreign protocol requests across a system area network, the computer program product comprising:

second instructions for encapsulating the request in a data packet; and

10

15

fifth instructions for encapsulating the second request in a second data packet; and

20

25

30

Docket No. AUS9-2000-0546-US1

fourth instructions for receiving a second request from a device utilizing a protocol which is foreign to the protocol utilized by the system area network;

5 fifth instructions for encapsulating the second request in a second data packet; and

sixth instructions, responsive to a determination that the first and second requests should be able to bypass the other, for sending the second data packet to a requested node via a second virtual lane on the system
10 area network fabric.

27. The computer program product as recited in claim 24, wherein the request is an interrupt received by a target channel adapter and further comprising:

15 fourth instructions for receiving the data packet, at a host channel adapter, and decoding the data packet to retrieve the interrupt; and

fifth instructions for interrupting the processor.

20 28. The computer program product as recited in claim 27, wherein the data packet is a first data packet and further comprising:

sixth instructions for receiving, at the host channel adapter, an end of interrupt instruction;

25 seventh instructions for encapsulating the end of interrupt instruction into a second data packet; and

eighth instructions for transmitting the second data packet to the target channel adapter via the system area network fabric.

30

29. The computer program product as recited in claim 28,

further comprising:

tenth instructions for decoding the second data packet to determine that the interrupt is complete.

10

fourth instructions for receiving, at the requested node, the data packet;

15

32. The computer program product as recited in claim 24, wherein the steps of receiving a request, encapsulating the request, and sending the data packet are performed by a host channel adapter.

20

25

30

Docket No. AUS9-2000-0546-US1

by a target channel adapter.

35. The computer program product as recited in claim 31,
wherein the instructions for receiving, at the requested
5 node, the data packet, decoding the data packet, and
transmitting the foreign protocol request are performed
by a host channel adapter.

36. The computer program product as recited in claim 31,
10 wherein the instructions for transmitting the foreign
protocol request comprises converting the request to an
appropriate host transaction.

37. The computer program product as recited in claim 24,
15 wherein the instructions for receiving a request,
encapsulating the request, and sending the data packet
are performed by a target channel adapter.

38. The computer program product as recited in claim 24,
20 wherein the requested node is a host channel adapter.

39. The computer program product as recited in claim 24,
wherein the instructions for encapsulating the foreign
protocol request comprises placing the request into a
25 data packet with appropriate headers and trailers in the
data packet to ensure that the data packet is delivered
across the system area network fabric to the requested
node.

30 40. The computer program product as recited in claim 31,
wherein the instructions for decoding the data packet

DOCKET 30000546

Docket No. AUS9-2000-0546-US1

comprises determining that the data packet contains a foreign protocol request and removing the foreign protocol request from the data packet.

- 5 41. A computer program product in a computer readable media for use in a data processing system for processing foreign protocol requests across a system area network, the computer program product comprising:

10 first instructions for receiving a data packet from a system area network fabric;

second instructions for determining that the data packet contains an encapsulated foreign protocol transmission;

15 third instructions for decoding the data packet to obtain the foreign protocol transmission; and

fourth instructions for sending the foreign protocol transmission to a requested device.

- 20 42. The computer program product as recited in claim 41, wherein the foreign protocol is a peripheral component interconnect bus protocol.

25 43. The computer program product as recited in claim 41, wherein the requested device is an input/output adapter.

30 44. The computer program product as recited in claim 41, wherein the instructions for receiving, determining, decoding, and sending are performed by a target channel adapter.

45. The computer program product as recited in claim 41,

DOCKET 9607260

Docket No. AUS9-2000-0546-US1

wherein the instructions for receiving, determining, decoding, and sending are performed by a host channel adapter.

5 46. The computer program product as recited in claim 45, wherein the instructions for sending comprises converting the foreign protocol request to an appropriate host transaction.

10 47. A system for processing foreign protocol requests across a system area network, the system comprising:
first means for receiving a request from a device utilizing a protocol which is foreign to a protocol utilized by the system area network;
15 second means for encapsulating the request in a data packet; and
third means for sending the data packet to a requested node via the system area network fabric.

20 48. The system as recited in claim 47, wherein the request is a first request, the data packet is a first data packet, and the sending the data packet comprises sending the data packet on a first virtual lane, and further comprising:

25 fourth means for receiving a second request from a device utilizing a protocol which is foreign to the protocol utilized by the system area network;
fifth means for encapsulating the second request in a second data packet; and
30 sixth means, responsive to a determination that the first and second requests are to be kept in order, for

Docket No. AUS9-2000-0546-US1

sending the second data packet to a requested node via the first virtual lane on the system area network fabric.

49. The system as recited in claim 47, wherein the request is a first request, the data packet is a first data packet, and the sending the data packet comprises sending the data packet on a first virtual lane, and further comprising:

fourth means for receiving a second request from a device utilizing a protocol which is foreign to the protocol utilized by the system area network;

fifth means for encapsulating the second request in a second data packet; and

sixth means, responsive to a determination that the first and second requests should be able to bypass the other, for sending the second data packet to a requested node via a second virtual lane on the system area network fabric.

50. The system as recited in claim 47, wherein the request is an interrupt received by a target channel adapter and further comprising:

fourth means for receiving the data packet, at a host channel adapter, and decoding the data packet to retrieve the interrupt; and

fifth means for interrupting the processor.

51. The system as recited in claim 50, wherein the data packet is a first data packet and further comprising:

sixth means for receiving, at the host channel adapter, an end of interrupt instruction;

Docket No. AUS9-2000-0546-US1

seventh means for encapsulating the end of interrupt instruction into a second data packet; and

5 eighth means for transmitting the second data packet to the target channel adapter via the system area network fabric.

52. The system as recited in claim 51, further comprising:

10 ninth means for receiving the second data packet;
tenth means for decoding the second data packet to determine that the interrupt is complete.

15 53. The system as recited in claim 47, wherein the foreign protocol is a peripheral component interconnect bus protocol.

54. The system as recited in claim 47, further comprising:

20 fourth means for receiving, at the requested node, the data packet;
fifth means for decoding the data packet to obtain the foreign protocol request; and
sixth means for transmitting the foreign protocol request to an appropriate device.

25 55. The system as recited in claim 47, wherein the steps of receiving a request, encapsulating the request, and sending the data packet are performed by a host channel adapter.

30 56. The system as recited in claim 47, wherein the

002002-00000000

requested node is a target channel adapter.

58. The system as recited in claim 54, wherein the means
10 for receiving, at the requested node, the data packet,
decoding the data packet, and transmitting the foreign
protocol request are performed by a host channel adapter.

60. The system as recited in claim 47, wherein the means
20 for receiving a request, encapsulating the request, and
sending the data packet are performed by a target channel
adapter.

62. The system as recited in claim 47, wherein the means for encapsulating the foreign protocol request comprises placing the request into a data packet with appropriate headers and trailers in the data packet to ensure that the data packet is delivered across the system area

network fabric to the requested node.

64. A system for processing foreign protocol requests
10 across a system area network, the system comprising:
first means for receiving a data packet from a
system area network fabric;
second means for determining that the data packet
contains an encapsulated foreign protocol transmission;
15 third means for decoding the data packet to obtain
the foreign protocol transmission; and
fourth means for sending the foreign protocol
transmission to a requested device.

66. The system as recited in claim 64, wherein the
25 requested device is an input/output adapter.

30

68. The system as recited in claim 64, wherein the means

Docket No. AUS9-2000-0546-US1

for receiving, determining, decoding, and sending are performed by a host channel adapter.

69. The system as recited in claim 68, wherein the means
5 for sending comprises converting the foreign protocol request to an appropriate host transaction.

002021-8661E260